

## GHCF | GeoSeal® High-Flow Coalescing Filter



### Features:

- Diesel fuel coalescing filter for dispensing, transfer or polishing filtration applications.
- Uses patented GeoSeal® elements.
- All-aluminum filter housing is fully compatible with diesel and biodiesel.
- Minimal clearance needed for element service, ideal for enclosure installations.
- Cartridge style element improves performance and reduces waste compared to spin-on solutions.
- A compact design with reduced dimensions compared to similar cartridge filter and spin-on solutions on the market.

### Markets:

- Bulk Fuel
- Industrial
- Mobile Vehicles
- Marine
- Mining
- Agriculture
- Power Gen.
- Rail Injector
- Fleet
- Railroad

### Specifications:

- **Flow Rating:**  
Up to 25 gpm (95 L/min)
- **Max. Operating Pressure:**  
150 psi (10.3 bar)
- **Min. Yield:**  
2600 psi (179 bar)
- **Temp. Range:**  
32°F to 225°F (0°C to 107°C) Standard  
-20°F to 225°F (-29°C to 107°C) Heater
- **Bypass Setting:**  
Cracking: 40 psi (2.8 bar)
- **Porting Head/Element Case/Sump:**  
Cast Aluminum, Anodized/  
Aluminum Anodized/  
Cast Aluminum, Anodized
- **Weight:**  
19.45 lbs. (8.82 kg)
- **Element Change Clearance:**  
4.5" (114 mm)