



How to Build a Valid Model Number for a Schroeder WQF15:



Example: NOTE: One option per box



BOX 1	BOX 2	BOX 3	BOX 4
Filter Series	Element Length (in)	Element Size and Media	Housing Seal Material
WQF15	39	QM60 = Q size 60 μ M media (reusable metal) QM150 = Q size 150 μ M media (reusable metal)	Omit = Buna N H = EPR V = Viton®

BOX 5	BOX 7
Porting Options	Dirt Alarm® Options
P48 = 3" NPTF	Omit = None
	D5 = Visual pop-up D9 = All stainless D5 (Recommended) D9C = D9 in cap (Recommended)
Bypass Setting	D8 = Visual w/ thermal lockout D8C = D8 in cap D8R = D8 opposite standard location
Omit = 30 psi cracking 50 = 50 psi cracking	MS5SS = All stainless MS5 Electrical w/ 12 in. 18 gauge 4-conductor cable MS10SS = All stainless MS10 Electrical w/ DIN connector (male end only)
	MS13SS = All stainless MS13 Supplied w/ threaded connector & light

Filter Model Number Selection



WKC50

WLF1

WKF5

WKFN5

WRLT

WQF5

WQF15

WQLF15

WKF3

WKL3

NOTES:

Box 2. Replacement element part numbers are a combination of Boxes 2 and 3, and the letter V.
Example: 39QM60V

Box 4. All elements for this filter are supplied with Viton® seals. Seal designation in Box 5 applies to housing only.
Viton® is a registered trademark of DuPont Dow Elastomers.

Box 7. D9/D9C indicator is the recommended option.