




Filter Model Number Selection



How to Build a Valid Model Number for a Schroeder WQLF15:



Example: NOTE: One option per box



BOX 1	BOX 2	BOX 3	BOX 4
Filter Series	Element Length (in)	Element Size and Media	Housing Seal Material
WQLF15	39	QM60 = Q size 60 μ M media (reusable metal) QM150 = Q size 150 μ M media (reusable metal)	Omit = Buna N H = EPR V = Viton®

BOX 5	BOX 6
Porting Options	Seal Material
P48 = 3" NPTF	Omit = 30 psi cracking 50 = 50 psi cracking

BOX 7	
Dirt Alarm® Options	
	Omit = None
Visual	D5 = Visual pop-up D5C = D5 in cap D9 = All stainless D5 (Recommended) D9C = D9 in cap (Recommended) DPG = Differential pressure gauge
Visual with Thermal Lockout	D8 = Visual w/ thermal lockout D8C = D8 in cap
Electrical	MS5 = Electrical w/ 12 in. 18 gauge 4-conductor cable MS5LC = Low current MS5 MS10 = Electrical w/ DIN connector (male end only) MS10LC = Low current MS10 MS11 = Electrical w/ 12 ft. 4-conductor wire MS12 = Electrical w/ 5 pin Brad Harrison connector (male end only) MS12LC = Low current MS12 MS16 = Electrical w/ weather-packed sealed connector MS16LC = Low current MS16 MS17LC = Electrical w/ 4 pin Brad Harrison male connector
Electrical with Thermal Lockout	MS5T = MS5 (see above) w/ thermal lockout MS5LCT = Low current MS5T MS10T = MS10 (see above) w/ thermal lockout MS10LCT = Low current MS10T MS12T = MS12 (see above) w/ thermal lockout MS12LCT = Low current MS12T MS16T = MS16 (see above) w/ thermal lockout MS16LCT = Low current MS16T MS17LCT = Low current MS17T
Electrical Visual	MS13 = Supplied w/ threaded connector & light MS14 = Supplied w/ 5 pin Brad Harrison connector & light (male end)
Electrical Visual with Thermal Lockout	MS13DCT = MS13 (see above), direct current, w/ thermal lockout MS13DCLCT = Low current MS13DCT MS14DCT = MS14 (see above), direct current, w/ thermal lockout MS14DCLCT = Low current MS14DCT

NOTES:

Box 2. Replacement element part numbers are a combination of Boxes 2 and 3, and the letter V.
Example: 39QM60V

Box 4. All elements for this filter are supplied with Viton® seals. Seal designation in Box 4 applies to housing only. Viton® is a registered trademark of DuPont Dow Elastomers.

Box 7. D9/D9C indicator is the recommended option.